



Pentospeed 0W-30 VS

Fully Synthetic Fuel Economy Motor Oil

Description

Pentospeed 0W-30 VS is an especially formulated fully synthetic fuel economy premium motor oil. By means of an additive combination of latest technology best antiwear characteristic is guaranteed and the particular base oil concept provides a very low evaporation loss. It is therefore preferably applicable to very demanding Audi-engines.

Pentospeed 0W-30 VS provides, due to its viscosity range, fuel savings in particular during winter operation and frequent cold weather starts. Furthermore optimal fuel economy is achieved by special friction modifiers leading to proven fuel saving results in API EC and MB 229.3 test runs.

Pentospeed 0W-30 VS can be used in gasoline and diesel engines with and

without turbochargers. It is miscible with all branded motor oils based on mineral, HC-synthetic or synthetic oils.

Quality Level

API SL/CF
ACEA A3/B4

Approvals

BMW Longlife-01
MB-Approval 229.3 / 229.5
VW-Specification 502 00 / 503 01 / 505 00

Product Classification

The product is not classified as dangerous.

Pentospeed 0W-30 VS		Typical Data	
	Unit	Result	Method
Appearance		bright and clear	DIN 10964
Density at 15 °C	kg/m ³	841	DIN EN ISO 12185
Kinematic Viscosity at 100 °C	mm ² /s	12,1	DIN EN ISO 3104
Kinematic Viscosity at 40 °C	mm ² /s	73	DIN EN ISO 3104
Viscosity Index		167	DIN ISO 2909
Dynamic Viscosity at -35 °C	mPa*s	5700	ASTM D5293
Pour Point	°C	-60	ISO 3016
Flash Point COC	°C	230	DIN EN ISO 2592

While handling lubricants the relevant safety rules have to be taken into account. For more detailed information please see the current safety data sheet for this product.

This product may not be available at all locations. For more information, please call us at +49 4103-9134-0 or visit us at www.pentosin.com
Due to continual product research and development, the information contained herein is subject to change without notification. Typical data may vary slightly.